



# SIP Extension Server 36

A07-VES3302-36

- Built-in Registrar and Proxy Server
- Supports up to 36 extensions
- Stackable up to 600 units
- Complete call management
- FAX Support

The A07-VES3302 are SIP extension servers for the Trunking Gateway. With built-in Registrar and Proxy Server; no other server is required. The A07-VES3302 line can be stacked up to 600 units, which is highly scalable for future upgrade. The extension server enables users to make calls between the SIP environment and IP PBX network, just like calls between extensions.



**E d g e - c o r e**

Powered by Accton

Edge-Core

TECHNICAL FEATURES		
Port Feature Fast	Ethernet Ports	2
	Extensions Server	36
Data/Voice Performance	Voice Compression (G.711)	Yes
	Voice Compression (G.729AB)	Yes
	Voice Compression (G.723)	Yes
	Silence Suppression (VAD, CNG)	Yes
	Jitter Buffer	Yes
	Echo Cancellation (G.165, G.168 16ms)	Yes
	Transport Protocol (RTP, RTCP)	Yes
	SIP Call Control Protocol	Yes
PBX Function	Call Transfer	Yes
	Call Forward	Yes
	Call Park	Support
	Inbound Transit Call	Yes
	Outbound Transit Call	Yes
	Network Operator Group	Yes
	Trunk Group	Yes
	CDR for Billing	Yes
	Works with traditional IP-PBX	Yes
	Stackable with Networking Functions	Yes
Management	Fax	Support
	Web configuration	Yes
	Telnet	Yes
Mechanical	FTP	Yes
	Dimension	172 x 35 x 176
Power Requirements	LED Indicator	Power, Alarm, Registered, Time Server, Stun, Link/Act, 100Mbps
	Power Type	External Power Adaptor
	Nominal Input Voltage	100VAC ~ 240VAC
	Input Frequency	50/60Hz
	Power Consumption	12W
Environmental	Operating Temperature	0° ~50° C
	Storage Temperature:	-10° to 70° C
	Humidity	95% maximum (Non condensing)



PRODUCT: SIP Extension Server36  
 PRODUCT CODE: A07-VES3302-36  
 EAN CODE: 8026974008363